

SYM76993VGGA

Intel® H61 micro ATX Board w VGA/2*Giga LAN/Audio/10COM

■ Features

- LGA1155 for Intel® i3/i5/i7/Pentium®/Celeron® Processors
- Intel® H61 PCH (Platform Controller Hub)
- 2 x 240pin DDR3 1600MHz/1333MHz DIMM up to 16GB
- 2 x PCI-E Gigabit LAN controller
- 4 x SATA II
- 10 x COM Ports , 10 x USB 2.0
- 1 x PCI-E x16, 1 x PCI-E x1, 2 x PCI slots

■ Specifications

>> System

Processor	LGA1155 for Intel® Core i3/i5/i7/Pentium®/Celeron® Processors Support Sandy Bridge and Ivy Bridge CPU
Chipset	Intel® H61 PCH
DRAM	2 x 240pin DDR3 1600/1333MHz DIMM up to 16GB
BIOS	32Mb AMI Flash ROM
Power Supply	Standard ATX power
Watchdog	Watchdog timer function
Dimension	244mm x 220mm

>> I/O Ports

HDD	4 x SATA 2.0
Serial Port	9 x RS232 + 1 x RS232/422/485 (Auto Flow control function) COM ports
Parallel	1 x LPT port support with ECP/EPP/SPP mode
Audio	Realtek ALC662 High Definition Audio, line-out, line-in and MIC
Keyboard/Mouse	1 x Mini-DIN port for PS/2 Keyboard and Mouse
LAN	2 x Realtek 8111E PCI-E Gigabit controller
USB	10 x USB2.0
Digital I/O	1 x 8 bits Digital I/O connector
Expansion	1 x PCI-Ex16, 1 x PCI-E x1, 2 x PCI slots

>> Display

Graphics	Intel® Integrated Graphics Engine with HD Graphics
VGA	1 x VGA port ,2048x1536 @ 75Hz max Resolution
DVI-D	1 x DVI-D port ,1920 x 1200@60Hz max Resolution

>> Environment

Operation Temperature	0°~60°C (32°~140°F)
Humidity	10~90%

■ Ordering Information

Model	SYM76993VGGA
Description	Intel® H61 micro ATX Board w VGA/DVI/2*Giga LAN/Audio/10COM

